

## NOTE


Rumble strips are not installed in certain reduced-width shoulder locations. See the SHOULDER TAPER DETAIL on Standard Plan H-4.





5" ± 1/2" 3/8" SECTION (A

TYPICAL SHOULDER INSTALLATION






SHEET 1 OF 2 SHEETS

APPROVED FOR PUBLICATION


Harold J. Peterfeso

03-11-03


NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED UPON REQUEST.



TYPE 2 ~ 12' GAP AND 12" WIDE STRIP TYPE 3 ~ 16' GAP AND 16" WIDE STRIP



TYPE 4 ~ 12" WIDE STRIP



## **RUMBLE STRIP PLACEMENT AT INTERSECTIONS**




## **SHOULDER RUMBLE STRIP TYPE 2, 3 AND 4** FOR UNDIVIDED HIGHWAYS **STANDARD PLAN H-4a**

SHEET 2 OF 2 SHEETS

APPROVED FOR PUBLICATION

Harold J. Peterfeso 03-11-03



NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE.
THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE
AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED UPON REQUEST.